



Benefits

- Pressure-sensitive film is the ideal choice for novelty stickers.
- Options range from an endless spectrum of brilliant colors, to an extensive array of specialty options like metallics, and holographics

Features

- 3.5 mil semi-flexible white vinyl film resists on-liner and applied shrinkage
- Printable via UV Offset, Solvent and UV Screen, Solvent and UV Inkjet, and Latex
- Permanent pressure-sensitive acrylic adhesive bonds well to a variety of surfaces including low surface energy plastics, paper, wood, glass and metal
- Backside printable tag stock release liner

Additional Details

Technical Data

Physical Properties

Thickness (Mils [microns])	Mils	Microns
Film	3.5 +/- 10 %	89
Adhesive	0.75-0.85 +/- 0.1	19-21 +/- 3
Liner	9.4 +/- 10 %	239

Test Method: ASTM D 3652 (Modified for use with non-tape product)



Adhesion Properties

Ultimate Peel from	Average Oz/In	(N/m)
Stainless Steel	33	363
Acrylic	46	506
Glass	30	330
Polypropylene	24	264

Test Method: ASTM D 903 (Modified for 72 hr. RT dwell time)

Additional Properties	Value	Test Method
Expected Shear	2	ASTM D 3654 Method A (1 hr. dwell, 1 sq. in, 4 lb. load)
Tack	350	ASTM D 2979
Expected Exterior Life	Two years	
Additional Information		
Service Temperature	-40°F to 176°F (-40°C to 80°C)	
Minimum Application Temperature	50°F (10°C)	
Storage Stability	Two years stored at 70°F (21°C) and 50% relative humidity	

Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.