



# Flexcon® FlexMount® Select™ DF132311

Graphic Mounting Film Clear Permanent/Permanent  
FLX000525

## Benefits

RoHS 2002/95/EC Compliant, RoHS 76/69/EEC Compliant, RoHS 2003/11/EC Compliant

## Features

1.0 mil double-faced optically clear polyester film ideal for applications requiring superior image quality

Permanent pressure-sensitive acrylic adhesive bonds well to printed surfaces

Adhesive offers excellent tack, clarity and wet out characteristics

Ultra-smooth polyester release liner provides ultimate smoothness and flow-out of adhesive on the overlaminating film

## Additional Details

## Technical Data

### Physical Properties

Thickness (Mils [microns])	Mils	Microns
Film		
Adhesive		
Liner		

Test Method:



# Flexcon® FlexMount® Select™ DF132311

Graphic Mounting Film Clear Permanent/Permanent  
FLX000525

## Adhesion Properties

Ultimate Peel from	Average Oz/In	(N/m)
--------------------	---------------	-------

Test Method:

Additional Properties	Value	Test Method
Expected Shear		
Tack		
Additional Information		
Service Temperature		
Minimum Application Temperature		
Storage Stability		

## Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.